




### 102GVE.1-I864



Pendant downlight with symmetrical light distribution to achieve an effective task, accent or ambient lighting.

Neutral cylindrical body in diameter 150mm.

Double Aluminium reflectors in assorted finishes. Top reflector: faceted metalized or sandblasted metalized depending on the beam angle outcome. Bottom reflector: sandblasted metalized.

Powder painted aluminium body available in assorted finishes, customized RAL under request.

Flush glass accessory available [reference M2.L0150]. Complete IP54 | IK05 fixture by ordering flush glass and IP rated connector accessories [reference F3.A3 (On/Off) / F3.A5 (DALI) ].

Drop glass disk accessory available in assorted colours [reference M1.A0150].

Drop metal disk accessory available in assorted colours [reference M1.B0150].

Built-in driver, included.

Passive temperature management: heat dissipation flows through an aluminium heat sink and the fixture body itself.

Suspended 1 meter by three steel cords. Transparent electrical wire.

Mounted to the ceiling by cylindrical ceiling rose.

For a more dynamic result, it can be supplied with an adapter for three-phase track [accessory reference M3.A].

GRAVITY can be combined with the BASE surface-mounted line to achieve a uniform effect.

**Light source power:** 11 W  
**Luminaire connected power:** 12.61 W  
**Constant Current:** 350 mA  
**Light source luminous flux:** 2040lm  
**Luminaire luminous flux:** 1856lm  
**CRI:** >80  
**Colour Temperature:** 3000K  
**Chromaticity Tolerance:** MacAdam 3  
**Beam Angle:** 24°  
**LOR:** 91%  
**Average Service Life:** 50000h  
**LED reliability:** 50000h L90B10  
**UGR:** <16  
**Photobiological safety group:** 1  
**Cd/Klm:** 3580  
**Luminaire efficiency:** 147 lm/W  
**Imax:** 7303 Cd

**This product contains a light source of energy efficiency class D**

#### Electronic Equipment


**S:** On/Off

**D:** DALI-2/switchDIM/corridorFUNCTION


\*Add the suffix **-S**, **-D** after the reference to indicate your electronic equipment choice.

#### Finishes

**2:** RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium, **1:** RAL9010: Pure White



#### Upgradeable, Replaceable, Repairable



#### Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 25.04.2024]

#### 5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346

BSI Cert ISO 14001:2015 - n°EMS 554685

#### ROVASI S.L.

Ronda de la Font Grossa, 15  
 Pol. Ind. La Gavarrà  
 08540 Centelles | Barcelona  
 Spain

#### Contact

T. +34 93 881 35 12 info@rovasi.com  
 T. +34 93 881 37 13 [www.rovasi.com](http://www.rovasi.com)