LEDA


Surface mounted downlights







835



110LDA.1.02-I721









Surface-mounted downlights with symmetrical light distribution to achieve an effective ambient lighting. Circular design available in 835mm diameter.

Powder painted one piece aluminium profile available in assorted finishes, customized RAL under request.

PMMA opal diffuser (thickness 3mm.).

Tridonic high energy efficiency printed circuit board. Tunable White PCB: 2700K - 6500K Built-in driver, included.

Electronic standard options for lighting control: SwitchDIM/ColourSwitch/DALI/DSI.

Passive temperature management: heat dissipation flows through the fixture body itself. Mounting to the ceiling plate with four securing points. Cable entry from the top of the fixture.

LEDA can be combined with PLACE pendant downlights and KUU and CANDRA recessed downlights to get a harmonious finish.

max=2569 Cd

1500

η=99.6% ▼ M ▼ Ø ▼ LUX

2

3 7.4 285

4

12.3

2.5 2569

4.9 642

9.8 161

Light source power: 58 W Fixture power: 59.9 W Constant Current: 250 mA

Luminous flux of the light source: 9610lm

Luminous flux of the fixture: 6605lm

CRI: >90

Colour Temperature: 2700K-6500K **Chromaticity Tolerance:** MacAdam 3

Beam Angle: 102°

Average Service Life: 50000h LED reliability: 50000h L90B50 Photobiological safety group: 1 Luminous efficacy: 110 lm/W

This product contains a light source of energy efficiency class D

Electronic Equipment

T: DALI-2/DSI SwitchDIM/ColourSwitch

*Add the suffix -T after the reference to indicate your electronic equipment choice.

Finishes

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 20.04.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346 BSI Cert ISO 14001:2015 - n°EMS 554685

ROVASIS.L.

T. +34 93 881 35 12 T. +34 93 881 37 13 info@rovasi.com www.rovasi.com