MOVE 100 Spots with recessed base





104MOV.1-R869



Recessed spots with symmetrical light distribution to achieve an effective task, accent or general lighting. Cylindrical design in diameter 90 mm.

Articulated arm adjustable 0°,15°, 30°, 45°, 60°, 75° and 90° and with 355° rotation around the vertical axis.


Facetted metalized or sandblasted metalized aluminium reflector.


Powder painted aluminium body and arm available in assorted finishes, customized RAL under request. Die-cast aluminium recessed base supplied with the same finish as the light fixture.

Optional anti-glare accessories for more visual comfort.

Remote driver included.

Passive temperature management: heat dissipation flows through aluminium heat sink. Mounted to the ceiling by two fixing points.








Light source power: 17 W Luminaire connected power: 18.33 W Constant Current: 500 mA Light source luminous flux: 2755lm Luminaire luminous flux: 2066lm **CRI:** >80 Colour Temperature: 2700K Chromaticity Tolerance: MacAdam 3 Beam Angle: 19° LOR: 75% Average Service Life: 50000h LED reliability: 50000h L90B10 **UGR:** <19 Photobiological safety group: 1 Luminaire efficiency: 113 lm/W This product contains a light source of energy efficiency class D

Electronic Equipment

K: On/Off (basic) S: On/Off (AC/DC) D: DALI-2/switchDIM/corridorFUNCTION D: DALI-2/switchDIM/corridorFUNCTION DE: DALI-2/switchDIM + 3h battery B: Bluetooth-Casambi



*Add the suffix -K, -S, -SE, -D, -DE, -B after the reference to indicate your electronic equipment choice.

Finishes

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 25.04.2024]

5 years guarantee

BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L.

Pol. Ind. La Gavarra

Spain

08540 Centelles | Barcelona

Contact Ronda de la Font Grossa, 15

T. +34 93 881 35 12 T. +34 93 881 37 13 info@rovasi.com www.rovasi.com