

# MOVE 100 OPTIMAL DISPLAY

# Spots with recessed base











# 107MOV.1-R1147



IP20 850°









lmax=14868 Cd

η=90.7% ▼ M ▼ Ø ▼ LUX

2

4 0.86 929

0.22 14868

1652

0.43 3717

0.65 3

1.08

Recessed spots with symmetrical light distribution to achieve an effective task, accent or general lighting. Special LED module created to be the optimal solution for specific projects.

Cylindrical design in diameter 120mm.

Articulated arm adjustable 0°,15°, 30°, 45°, 60°, 75° and 90° and with 355° rotation around the vertical

Facetted metalized or sandblasted metalized aluminium reflector.

Powder painted aluminium body and arm available in assorted finishes, customized RAL under request.

Die-cast aluminium recessed base supplied with the same finish as the light fixture.

Optional anti-glare accessories for more visual comfort.

Remote driver included.

Passive temperature management: heat dissipation flows through aluminium heat sink.

Mounted to the ceiling by two fixing points.

Light source power: 11 W Fixture power: 12.61 W Constant Current: 350 mA

Luminous flux of the light source: 1635lm

Luminous flux of the fixture: 1488lm

**CRI:** >90

Colour Temperature: GOLD

Chromaticity Tolerance: MacAdam 3

Beam Angle: 12°

**LOR:** 91%

Average Service Life: 50000h LED reliability: 50000h L90B50

**UGR:** <19

Photobiological safety group: 1 Luminous efficacy: 118 lm/W

This product contains a light source of energy efficiency class E

### **Electronic Equipment**

K: On/Off (basic)

S: On/Off (AC/DC) SE: On/Off (AC/DC) + Battery 3h

D: DALI-2/switchDIM/corridorFUNCTION
DE: DALI-2/switchDIM + 3h battery

B: Bluetooth-Casambi

\*Add the suffix -K, -S, -SE, -D, -DE, -B after the reference to indicate your electronic equipment choice.

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

# Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 24.04.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

## **ROVASIS.L.**

### Contact

T. +34 93 881 35 12

info@rovasi.com

T. +34 93 881 37 13 www.rovasi.com