MOVE 100 OPTIMAL DISPLAY

Spots with recessed base



η=90.7% ▼ M ▼ Ø ▼ LUX

2

3

4 0.86 602


0.22 9639


0.43 2410

0.65 1071

1.08









107MOV.1-R1149



IP20 850°











Recessed spots with symmetrical light distribution to achieve an effective task, accent or general lighting. Special LED module created to be the optimal solution for specific projects.

Cylindrical design in diameter 120mm.

Articulated arm adjustable 0°,15°, 30°, 45°, 60°, 75° and 90° and with 355° rotation around the vertical

Facetted metalized or sandblasted metalized aluminium reflector.

Powder painted aluminium body and arm available in assorted finishes, customized RAL under request.

Die-cast aluminium recessed base supplied with the same finish as the light fixture.

Optional anti-glare accessories for more visual comfort.

Remote driver included.

Passive temperature management: heat dissipation flows through aluminium heat sink.

Mounted to the ceiling by two fixing points.

Light source power: 11 W Fixture power: 12.61 W Constant Current: 350 mA

Luminous flux of the light source: 1060lm

Luminous flux of the fixture: 965lm

CRI: >90

Colour Temperature: FRESH MEAT Chromaticity Tolerance: MacAdam 4

Beam Angle: 12°

LOR: 91%

Average Service Life: 50000h LED reliability: 50000h L90B50

UGR: <16

Photobiological safety group: 1 Luminous efficacy: 77 lm/W

Electronic Equipment

K: On/Off (basic) S: On/Off (AC/DC)

SE: On/Off (AC/DC) + Battery 3h
D: DALI-2/DSI switchDIM/corridorFUNCTION

DE: DALI-2/DSI switchDIM + 3h battery B: Bluetooth-Casambi

*Add the suffix -K, -S, -SE, -D, -DE, -B after the reference to indicate your electronic equipment choice.

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 19.04.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L.

Contact

T. +34 93 881 35 12 T. +34 93 881 37 13 info@rovasi.com www.rovasi.com