

MOVE 100

Spots with recessed base











107MOV.1-R881













lmax=23752 Cd

η=91.3% ▼ M ▼ Ø ▼ LUX

1

2 0.57 5938

4

0.28 23752

1484 1.13

0.85

1.42 950 16°

Recessed spots with symmetrical light distribution to achieve an effective task, accent or general lighting. Cylindrical design in diameter 120mm.

Articulated arm adjustable 0°,15°, 30°, 45°, 60°, 75° and 90° and with 355° rotation around the vertical

Facetted metalized or sandblasted metalized aluminium reflector.

Powder painted aluminium body and arm available in assorted finishes, customized RAL under request.

Die-cast aluminium recessed base supplied with the same finish as the light fixture.

Optional anti-glare accessories for more visual comfort.

Remote driver included.

Passive temperature management: heat dissipation flows through aluminium heat sink.

Mounted to the ceiling by two fixing points.

Light source power: 23 W Luminaire connected power: 25.33 W

Constant Current: 700 mA Light source luminous flux: 3900lm Luminaire luminous flux: 3549lm

CRI: >80

Colour Temperature: 2700K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 12° **LOR:** 91%

Average Service Life: 50000h LED reliability: 50000h L90B10

UGR: <19

Photobiological safety group: 1 Luminaire efficiency: 140 lm/W

This product contains a light source of energy efficiency class D

Electronic Equipment

K: On/Off (basic)
S: On/Off (AC/DC)

SE: On/Off (AC/DC) + Battery 3h
D: DALI-2/switchDIM/corridorFUNCTION
DE: DALI-2/switchDIM + 3h battery

B: Bluetooth-Casambi

Finishes

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 25.04.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASIS.L.

T. +34 93 881 35 12

info@rovasi.com www.rovasi.com

T. +34 93 881 37 13

^{*}Add the suffix -K, -S, -SE, -D, -DE, -B after the reference to indicate your electronic equipment choice.