

MOVE 100

Spots with recessed base









111MOV.1-R870



IP20 850°









lmax=26098 Cd

η=90.7% ▼ M ▼ Ø ▼ LUX

1

2 0.43 6524

3 0.65

4

1.08 1044

0.22 26098

1631 0.86

12°

Recessed spots with symmetrical light distribution to achieve an effective task, accent or general lighting. Cylindrical design in diameter 140 mm.

Articulated arm adjustable 0°,15°, 30°, 45°, 60°, 75° and 90° and with 355° rotation around the vertical

Facetted metalized or sandblasted metalized aluminium reflector.

Powder painted aluminium body and arm available in assorted finishes, customized RAL under request.

Die-cast aluminium recessed base supplied with the same finish as the light fixture.

Optional anti-glare accessories for more visual comfort.

Remote driver included.

Passive temperature management: heat dissipation flows through aluminium heat sink.

Mounted to the ceiling by two fixing points.

Light source power: 17 W Fixture power: 18.33 W Constant Current: 500 mA

Luminous flux of the light source: 2870lm Luminous flux of the fixture: 2612lm

CRI: >80

Colour Temperature: 3000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 12° **LOR:** 91%

Average Service Life: 50000h

LED reliability: 50000h L90B10

UGR: <16

Photobiological safety group: 1 Luminous efficacy: 142 lm/W

This product contains a light source of energy efficiency class D

Electronic Equipment

K: On/Off (basic)
S: On/Off (AC/DC)

SE: On/Off (AC/DC) + Battery 3h
D: DALI-2/switchDIM/corridorFUNCTION
DE: DALI-2/switchDIM + 3h battery

B: Bluetooth-Casambi

Finishes

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 24.04.2024]

5 years guarantee



Spain

T. +34 93 881 37 13

Contact

^{*}Add the suffix -K, -S, -SE, -D, -DE, -B after the reference to indicate your electronic equipment choice.