

MOVE 300 OPTIMAL DISPLAY

Surface-mounted spots












307MOV.1-I1149



IP20 850°





Special LED module created to be the optimal solution for specific projects.

. Cylindrical design in diameter 120mm.

Articulated arm adjustable 0°,15°, 30°, 45°, 60°, 75° and 90° and with 355° rotation around the vertical

Facetted metalized or sandblasted metalized aluminium reflector.

Powder painted aluminium body and arm available in assorted finishes, customized RAL under request. Aluminium base for attachment to the ceiling supplied with the same finish as the light fixture.

Imax=9639 Cd

η=90.7% ▼ M ▼ Ø ▼LUX

4

0.22 9639

0.43 2410

0.86 602

1.08 386 12°

Optional anti-glare accessories for more visual comfort.

Integral driver included.

Passive temperature management: heat dissipation flows through aluminium heat sink.

Mounted to the ceiling by two fixing points.

Light source power: 11 W

Luminaire connected power: 12.61 W

Constant Current: 350 mA

Light source luminous flux: 1060lm Luminaire luminous flux: 965lm

CRI: >90

Colour Temperature: FRESH MEAT Chromaticity Tolerance: MacAdam 4

Beam Angle: 12°

LOR: 91%

Average Service Life: 50000h LED reliability: 50000h L90B50

Photobiological safety group: 1 Luminaire efficiency: 77 lm/W

Electronic Equipment

S: On/Off
D: DALI-2/switchDIM/corridorFUNCTION

*Add the suffix -S, -D after the reference to indicate your electronic equipment choice.

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 27.04.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASIS.L.

Contact

T. +34 93 881 35 12

info@rovasi.com www.rovasi.com

T. +34 93 881 37 13