

MOVE 300 OPTIMAL DISPLAY


Surface-mounted spots

ROVASI
Positive Lighting










307MOV.1-I684

IP20 | 850º | +ELEC | +INSTAL | +RAL

Surface-mounted spots with symmetrical light distribution to achieve an effective task, accent or general lighting.
Special LED module created to be the optimal solution for specific projects.
Cylindrical design in diameter 120mm.
Articulated arm adjustable 0º,15º, 30º, 45º, 60º, 75º and 90º and with 355º rotation around the vertical axis.
Facetted metalized or sandblasted metalized aluminium reflector.
Powder painted aluminium body and arm available in assorted finishes, customized RAL under request.
Aluminium base for attachment to the ceiling supplied with the same finish as the light fixture.
Optional anti-glare accessories for more visual comfort.
Integral driver included.
Passive temperature management: heat dissipation flows through aluminium heat sink.
Mounted to the ceiling by two fixing points.

Light source power: 17 W
Fixture power: 18,33 W
Constant Current: 500 mA
Luminous flux of the light source: 2030lm
Luminous flux of the fixture: 1847lm
CRI: >90
Colour Temperature: GOLD
Chromaticity Tolerance: MacAdam 3
Beam Angle: 12º
LOR: 91%
Average Service Life: 50000h
LED reliability: 50000h L90B50
Photobiological safety group: 1
Luminous efficacy: 101 lm/W
This product contains a light source of energy efficiency class E





▼M	▼Ø	▼LUX	12°
1	0.22	18459	
2	0.43	4615	
3	0.65	2051	
4	0.86	1154	
5	1.08	738	

Electronic Equipment
S: On/Off
D: DALI-2
There are accessories available for dimming devices.
*Add the suffix **-S, -D** after the reference to indicate your electronic equipment choice.

Finishes
1: RAL9010: Pure White, **2:** RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium

Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 29.03.2024]

5 years guarantee

CE

BSI Cert ISO 9001:2015 - nºFM 39346
BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L.
Ronda de la Font Grossa, 15
Pol. Ind. La Gavarra
08540 Centelles | Barcelona
Spain

Contact
T. +34 93 881 35 12 info@rovasi.com
T. +34 93 881 37 13 **www.rovasi.com**