

MOVE 300 OPTIMAL DISPLAY



Surface-mounted spots









307MOV.1-I687



Surface-mounted spots with symmetrical light distribution to achieve an effective task, accent or general lighting.

Special LED module created to be the optimal solution for specific projects.

Cylindrical design in diameter 120mm. Articulated arm adjustable 0°,15°, 30°, 45°, 60°, 75° and 90° and with 355° rotation around the vertical axis.

Facetted metalized or sandblasted metalized aluminium reflector.

Powder painted aluminium body and arm available in assorted finishes, customized RAL under request. Aluminium base for attachment to the ceiling supplied with the same finish as the light fixture. Optional anti-glare accessories for more visual comfort.

Imax=13367 Cd

n=90.7% ▼M ▼Ø ▼LUX

0.22 13367

0.86 835

1485

1

2 0.43 3342

3 0.65

4

5 1.08 535

12°

Integral driver included.

Passive temperature management: heat dissipation flows through aluminium heat sink. Mounted to the ceiling by two fixing points.

Light source power: 17 W

Fixture power: 18,33 W Constant Current: 500 mA Luminous flux of the light source: 1470lm Luminous flux of the fixture: 1338lm CRI: >90 Colour Temperature: GOLD+ Chromaticity Tolerance: MacAdam 4 Beam Angle: 12° LOR: 91% Average Service Life: 50000h LED reliability: 50000h L90B50 UGR: <16 Photobiological safety group: 1 Luminous efficacy: 73 lm/W This product contains a light source of energy efficiency class G



S: On/Off D: DALI-2/DSI switchDIM/corridorFUNCTION

*Add the suffix -S, -D after the reference to indicate your electronic equipment choice.

Finishes

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 20.04.2024]

5 years guarantee

BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L.

Spain

Pol. Ind. La Gavarra

Ronda de la Font Grossa, 15

08540 Centelles | Barcelona

Contact

T. +34 93 881 35 12 T. +34 93 881 37 13 info@rovasi.com www.rovasi.com