

# MOVE 300 OPTIMAL DISPLAY

# Surface-mounted spots











# 311MOV.1-I684







Surface-mounted spots with symmetrical light distribution to achieve an effective task, accent or general

Special LED module created to be the optimal solution for specific projects.

. Cylindrical design in diameter 140 mm.

Articulated arm adjustable 0°,15°, 30°, 45°, 60°, 75° and 90° and with 355° rotation around the vertical

Facetted metalized or sandblasted metalized aluminium reflector.

Powder painted aluminium body and arm available in assorted finishes, customized RAL under request. Aluminium base for attachment to the ceiling supplied with the same finish as the light fixture.

Imax=18459 Cd

η=90.7% ▼ M ▼ Ø ▼LUX

1

4

0.22 18459

0.43 4615

0.86 1154

1.08

Optional anti-glare accessories for more visual comfort.

Integral driver included.

Passive temperature management: heat dissipation flows through aluminium heat sink.

Mounted to the ceiling by two fixing points.

Light source power: 17 W Fixture power: 18,33 W Constant Current: 500 mA

Luminous flux of the light source: 2030lm Luminous flux of the fixture: 1847lm

**CRI:** >90

Colour Temperature: GOLD

Chromaticity Tolerance: MacAdam 3

Beam Angle: 12°

**LOR:** 91%

Average Service Life: 50000h LED reliability: 50000h L90B50 Photobiological safety group: 1 Luminous efficacy: 101 lm/W

This product contains a light source of energy efficiency class E

# **Electronic Equipment**

S: On/Off
D: DALI-2/DSI switchDIM/corridorFUNCTION

\*Add the suffix -S, -D after the reference to indicate your electronic equipment choice.

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

## Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 20.04.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

### **ROVASI S.L.**

Ronda de la Font Grossa, 15 Pol. Ind. La Gavarra 08540 Centelles | Barcelona Spain

### Contact

T. +34 93 881 35 12 T. +34 93 881 37 13 info@rovasi.com www.rovasi.com