
# MOVE 900


# Track spots













# 907MOV.1-T864











Track spots with symmetrical light distribution to achieve an effective task, accent or general lighting. Cylindrical design in diameter 120mm.

Articulated arm adjustable 0°,15°, 30°, 45°, 60°, 75° and 90° and with 355° rotation around the vertical axis.

Facetted metalized or sandblasted metalized aluminium reflector.

Powder painted aluminium body and arm available in assorted finishes, customized RAL under request.

Track adaptor available in white, black or grey.

Optional anti-glare accessories for more visual comfort.

Driver built into the track adaptor. Consult compatible tracks with the track adaptor. Passive temperature management: heat dissipation flows through aluminium heat sink.

Three-phase tracks are available as well as accessories to create a custom system.

Light source power: 11 W Fixture power: 12.61 W Constant Current: 350 mA

Luminous flux of the light source: 2040lm Luminous flux of the fixture: 1856lm

**CRI:** >80

Colour Temperature: 3000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 12° LOR: 91%

Average Service Life: 50000h LED reliability: 50000h L90B10 Photobiological safety group: 1 Luminous efficacy: 147 lm/W

This product contains a light source of energy efficiency class D

#### 

## **Electronic Equipment**

S: On/Off

D: DALI-2/DSI/switchDIM

B: Bluetooth Casambi

\*Add the suffix -S, -D, -B after the reference to indicate your electronic equipment choice.

## Finishes

1: RAL9010: Pure White, 2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium ( resistant to the glow wire test 750°)

# Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 29.03.2024]

5 years guarantee



BSI Cert ISO 14001:2015 - nºEMS 554685