

## 111VRL.1.02-I722



Semi-recessed downlights with symmetrical light distribution to achieve an effective ambient lighting. Circular design available in 1155mm diameter.

Powder painted one piece aluminium profile available in assorted finishes, customized RAL under request.

PMMA opal diffuser (thickness 3mm.).

Tridonic high energy efficiency printed circuit board. Tunable White PCB: 2700K - 6500K

Built-in driver, included.

Electronic standard options for lighting control: SwitchDIM/ColourSwitch/DALI/DSI.

Passive temperature management: heat dissipation flows through the fixture body itself.

Ceiling-mounted using galvanised steel support with screws, ceiling thickness up to 25mm.

LEDA can be combined with PLACE pendant downlights and KUJ and CANDRA recessed downlights to get a harmonious finish.

**Light source power:** 102 W

**Fixture power:** 105,5 W

**Constant Current:** 250 mA

**Luminous flux of the light source:** 17600lm

**Luminous flux of the fixture:** 14960lm

**CRI:** >90

**Colour Temperature:** 2700K-6500K

**Chromaticity Tolerance:** MacAdam 3

**Beam Angle:** 108°

**Average Service Life:** 50000h

**LED reliability:** 50000h L90B50

**Photobiological safety group:** 1

**Luminous efficacy:** 142 lm/W

**This product contains a light source of energy efficiency class D**


### Electronic Equipment

**T:** DALI-2/DSI SwitchDIM/ColourSwitch

\*Add the suffix **-T** after the reference to indicate your electronic equipment choice.

### Finishes

**2:** RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium, **1:** RAL9010: Pure White



### Upgradeable, Replaceable, Repairable



#### Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 16.04.2024]

#### 5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346

BSI Cert ISO 14001:2015 - n°EMS 554685

#### ROVASI S.L.

Ronda de la Font Grossa, 15  
Pol. Ind. La Gavarra  
08540 Centelles | Barcelona  
Spain

#### Contact

T. +34 93 881 35 12  
T. +34 93 881 37 13

info@rovasi.com

www.rovasi.com