# **ACTIVO OPTIMAL DISPLAY**

# Adjustable recessed downlights



η=90.9% ▼ M ▼ Ø ▼ LUX

2

3 1.27


4 1.69 393


0.42 6283

0.85 1571

2.1 251 24°







## 102ACT.1-R1151



IP20 850°











Imax=6283 Cd

Recessed ceiling-mounted downlight with symmetrical light distribution to achieve an effective task, accent or ambient lighting.

Adjustable to 20°.

Circular design in diameter 160mm.

Aluminium reflector in assorted finishes: facetted metalized or sandblasted metalized depending on the beam angle outcome.

Powder painted die-cast aluminium trim available in assorted finishes, customized RAL under request. Remote driver supplied. LED module for special applications.

Electronic options for lighting control: DALI-2.

Passive temperature management: heat dissipation flows through an aluminium heat sink diffuser. Ceiling-mounted using galvanised steel support with screws, ceiling thickness up to 40mm.

Light source power: 11 W Luminaire connected power: 12.61 W

Constant Current: 350 mA Light source luminous flux: 1755lm Luminaire luminous flux: 1597lm

**CRI:** >90

Colour Temperature: FISH

Chromaticity Tolerance: MacAdam 3

Beam Angle: 24° **LOR:** 91%

Average Service Life: 50000h LED reliability: 51000h L80B10 Photobiological safety group: 1

**Cd/Klm:** 3580

This product contains a light source of energy efficiency class E

# **Electronic Equipment**

K: On/Off (basic)
S: On/Off (AC/DC + looping through) SE: On/Off (AC/DC+looping) + 3h battery
D: DALI-2/switchDIM/corridorFUNCTION
DE: DALI-2/switchDIM/corridorFUNCTION + Battery 3h

\*Add the suffix -K, -S, -SE, -D, -DE, -B after the reference to indicate your electronic equipment choice.

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

### Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 26.04.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

#### **ROVASI S.L.**

T. +34 93 881 37 13

info@rovasi.com www.rovasi.com

T. +34 93 881 35 12