DYNAMIC OPTIMAL DISPLAY

Adjustable recessed downlights



η=90.7% ▼ M ▼ Ø ▼ LUX

1

3 0.65


4 0.86 628


0.22 10048

0.43 2512

1.08 402 12°







105DNM.1-R1148





(m

Adjustable to 20° and 180°+180° rotation.

Circular design in diameter 165mm.

Aluminium reflector in assorted finishes: facetted metalized or sandblasted metalized depending on the beam angle outcome.

Powder painted aluminium trim available in assorted finishes, customized RAL under request.

Remote driver supplied. LED module for special applications.

Electronic options for lighting control: DALI/DSI.

Passive temperature management: heat dissipation flows through an aluminium heat sink diffuser. Ceiling-mounted using galvanised steel support with screws, ceiling thickness up to 40mm.

lmax=10048 Cd

Light source power: 11 W Fixture power: 12.61 W Constant Current: 350 mA

Luminous flux of the light source: 1105lm Luminous flux of the fixture: 1005lm

CRI: >90

Colour Temperature: GOLD+

Chromaticity Tolerance: MacAdam 4

Beam Angle: 12° **LOR:** 91%

Average Service Life: 50000h LED reliability: 51000h L80B10 Photobiological safety group: 1

Cd/Klm: 9093

This product contains a light source of energy efficiency class G

Electronic Equipment

K: On/Off (basic)
S: On/Off (AC/DC + looping through) SE: On/Off (AC/DC+looping) + 3h battery
D: DALI-2/DSI switchDIM/corridorFUNCTION

DE: DALI-2/DSI switchDIM/corridorFUNCTION + Battery 3h

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 18.04.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L.

Contact

T. +34 93 881 35 12 T. +34 93 881 37 13 info@rovasi.com www.rovasi.com

^{*}Add the suffix -K, -S, -SE, -D, -DE after the reference to indicate your electronic equipment choice.