

143TMB.1.01-I1170



Surface mounted fixtures with symmetrical light distribution. Wall fixtures with light emission on one side. Cylindrical design in diameter 120mm.
Protection rating against dust and moisture: entire IP65.
Protection rating of resistance to harmful mechanical impacts: IK07.
Robust body and trim made of die-cast aluminium coated with polyester powder along with C4 treatment for corrosion resistance to guarantee further durability. Textured paint finish. Different RAL colour finishes available under request. C5-M special coating for highly corrosive environments is available under request.
Facetted metalized aluminium reflector.
5 mm tempered protection glass clear as standard, other finishes under request.
Polycarbonate diffuser as option to achieve IK10 protection degree.
Temperature resistant silicone rubber gasket.
Anti-condensation device.
A4 stainless steel locking screw. Optional supply of A2 stainless steel vandal-resistant screws [reference F2.A0120+F2.A1].
Built-in driver, included.
Electronic options for lighting control: DALI.
Passive temperature management: heat dissipation flows through the fixture body itself or through interior aluminium heat sink.
Mounting to the wall through mounting plate with two fixing holes.
Cable entry from the mounting plate.

Light source power: 9.7 W

Fixture power: 10.74 W

Constant Current: 300 mA

Luminous flux of the light source: 1750lm

Luminous flux of the fixture: 1134lm

CRI: >80

Colour Temperature: 3000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 19°

LOR: 68%


Average Service Life: 50000h

LED reliability: 50000h L90B10

Photobiological safety group: 1

Luminous efficacy: 106 lm/W

This product contains a light source of energy efficiency class D



Electronic Equipment

S: On/Off


D: DALI-2/DSI switchDIM/corridorFUNCTION

*Add the suffix **-S**, **-D** after the reference to indicate your electronic equipment choice.

Finishes

1: RAL9010: Pure White textured, **2:** RAL9005: Jet Black textured, **4:** RAL7016: Anthracite Grey textured, **7:** RAL9006: White Aluminium textured

Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 18.04.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346
BSI Cert ISO 14001:2015 - n°EMS 554685

ROVASI S.L.

Ronda de la Font Grossa, 15
Pol. Ind. La Gavarra
08540 Centelles | Barcelona
Spain

Contact

T. +34 93 881 35 12 info@rovasi.com
T. +34 93 881 37 13 www.rovasi.com