
# AERIAL

IP65 Pendant downlights for catenary systems

ROVASI
Positive Lighting







## 123ARL.1.01-I1168

IP65 | IK07 | 850º | +IK | +ELEC | +INSTAL | +RAL | 2.215Kg

Pendant downlights with symmetrical light distribution.
Cylindrical design in diameter 120mm.
Protection rating against dust and moisture: entire IP65.
Protection rating of resistance to harmful mechanical impacts: IK07.
Robust body and trim made of die-cast aluminium coated with polyester powder along with C4 treatment for corrosion resistance to guarantee further durability. Textured paint finish. Different RAL colour finishes available under request. C5-M special coating for highly corrosive environments is available under request.
Facetted metalized aluminium reflector.
5 mm tempered protection glass clear as standard, other finishes under request.
Polycarbonate diffuser as option to achieve IK10 protection degree.
Temperature resistant silicone rubber gasket.
Anti-condensation device.
A4 stainless steel locking screw. Optional supply of A2 stainless steel vandal-resistant screws [reference F2.A0120+F2.A1].
Built-in driver, included.
Electronic options for lighting control: DALI.
Passive temperature management: heat dissipation flows through the fixture body itself or through interior aluminium heat sink.
Cable hanger made in stainless steel 316L. Adjustable 0º, 5º, 10º,15º or 20º to compensate for sloping catenary system.





| ▼M | ▼Ø | ▼LUX | 25º |
|---|---|---|---|
| 1 | 0.45 | 3168 | |
| 2 | 0.89 | 792 | |
| 3 | 1.34 | 352 | |
| 4 | 1.78 | 198 | |
| 5 | 2.2 | 127 | |


**Light source power:** 8 W
**Fixture power:** 8.89 W
**Constant Current:** 250 mA
**Luminous flux of the light source:** 1530lm
**Luminous flux of the fixture:** 1033lm
**CRI:** >80
**Colour Temperature:** 4000K
**Chromaticity Tolerance:** MacAdam 3
**Beam Angle:** 25º
**LOR:** 68%
**Average Service Life:** 50000h
**LED reliability:** 50000h L90B10
**Photobiological safety group:** 1
**Luminous efficacy:** 116 lm/W
**This product contains a light source of energy efficiency class** D

**Electronic Equipment**
**S:** On/Off
**D:** DALI-2
There are accessories available for dimming devices.
*Add the suffix **-S, -D** after the reference to indicate your electronic equipment choice.

**Finishes**
**1:** RAL9010: Pure White textured, **2:** RAL9005: Jet Black textured, **4:** RAL7016: Anthracite Grey textured, **7:** RAL9006: White Aluminium textured

**Upgradeable, Replaceable, Repairable**



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 28.03.2024]

**5 years guarantee**

CE

BSI Cert ISO 9001:2015 - nºFM 39346
BSI Cert ISO 14001:2015 - nºEMS 554685

**ROVASI S.L.**
Ronda de la Font Grossa, 15
Pol. Ind. La Gavarra
08540 Centelles | Barcelona
Spain

**Contact**
T. +34 93 881 35 12 info@rovasi.com
T. +34 93 881 37 13 **www.rovasi.com**