
SUMMIT Pendant downlights





101SMM.1-I867

Light source power: 11 W

Constant Current: 350 mA

Colour Temperature: 3000K

Average Service Life: 50000h LED reliability: 50000h L90B10

Photobiological safety group: 1

Luminous efficacy: 125 lm/W

Fixture power: 12.61 W

CRI: >90

LOR: 91%

UGR: <16

Cd/Klm: 9093

Beam Angle: 12°



Pendant downlight with symmetrical light distribution to achieve an effective task or ambient lighting. Facetted metallized aluminium reflector to control and direct the light. Powder painted aluminium body available in assorted finishes, customized RAL under request. Built-in driver, included.

Electronic options for lighting control: DALI/DSI.

Luminous flux of the light source: 1730lm

Luminous flux of the fixture: 1574lm

Chromaticity Tolerance: MacAdam 3

Passive temperature management: heat dissipation flows through an aluminium heat sink and the fixture body itself.

Delivered with 1 meter steel cord suspension as standard and Transparent electronic wire. Mounted to the ceiling by cylindrical ceiling rose.

For a more dynamic result, it can be supplied with an adapter for three-phase track [reference M3.B].

lmax=15731 Cd η=90.7% ▼M ▼Ø ▼LUX 1 0.22 15731 3000 2 0.43 3933 6000 3 0.65 1748 9000 4 0.86 983 2000 5 1.08 629 5000

This product contains a light source of energy efficiency class $\ensuremath{\mathsf{E}}$

Electronic Equipment

Imax: 15731 Cd

S: On/Off D: DALI-2/DSI switchDIM/corridorFUNCTION

*Add the suffix -S, -D after the reference to indicate your electronic equipment choice.

Finishes

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 17.04.2024]

5 years guarantee

BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685 ROVASI S.L. Ronda de la Font Grossa, 15 Pol. Ind. La Gavarra 08540 Centelles | Barcelona Spain

Contact

T. +34 93 881 35 12 T. +34 93 881 37 13 info@rovasi.com www.rovasi.com