
SUMMIT Pendant downlights





101SMM.1-I870



Pendant downlight with symmetrical light distribution to achieve an effective task or ambient lighting. Facetted metallized aluminium reflector to control and direct the light. Powder painted aluminium body available in assorted finishes, customized RAL under request. Built-in driver, included. Electronic options for lighting control: DALI-2. The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM \leq 1 and SVM \leq 0.4. Passive temperature management: heat dissipation flows through an aluminium heat sink and the fixture body itself. Delivered with 1 meter steel cord suspension as standard and Transparent electronic wire. Mounted to the ceiling by cylindrical ceiling rose. For a more dynamic result, it can be supplied with an adapter for three-phase track [reference M3.B]. max=26098 Cd Luminaire luminous flux: 2612lm η=90.7% ▼M ▼Ø ▼LUX Luminaire connected power: 18.33 W 0.22 26098 1 Luminaire efficiency: 142 lm/W 000 0.43 6524 2 Light source luminous flux: 2870lm 10000 Light source power: 17 W 0.65 2900 3 15000 Constant Current: 500 mA 0.86 1631 4 **CRI:** >80 20000 Colour Temperature: 3000K 5 1.08 1044 5000 Chromaticity Tolerance: MacAdam 3 Beam Angle: 12° LOR: 91% LED reliability at nominal Ta = 25°C: 50000h L90B10 **UGR:** <16 Photobiological safety group: 1 Cd/Klm: 9093 Imax: 26097 Cd This product contains a light source of energy efficiency class D **Electronic Equipment** S: On/Off D: DALI-2/switchDIM/corridorFUNCTION *Add the suffix -S, -D after the reference to indicate your electronic equipment choice. Finishes 1: RAL9010: Pure White, 2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium

Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 04.07.2025]

5 years guarantee

C E BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L.

Pol. Ind. La Gavarra

Spain

Ronda de la Font Grossa, 15

08540 Centelles | Barcelona

Contact

T. +34 93 881 35 12 T. +34 93 881 37 13 info@rovasi.com www.rovasi.com

