

STYLE Small recessed downlights









111STY.50-R938



Recessed ceiling-mounted downlights with symmetrical light distribution to achieve an effective task or ambient lighting.

Round design in diameter 55mm.

Die-cast aluminium trim liquid-painted in appealing textured finishes.


Accessory available to increase the protection rating to IP44 from underneath [reference M2.A0035]. Honeycomb anti-dazzle screen accessory to increase visual comfort [reference M6.A0035]. Remote driver included.

Passive temperature management: heat dissipation via aluminium heat sink.

Ceiling-mounted using galvanised steel support with spring clamps.

Light source power: 4.9 W

Luminaire connected power: 5.45 W Constant Current: 150 mA Light source luminous flux: 690lm Luminaire luminous flux: 469lm **CRI:** >90 Colour Temperature: 3000K Chromaticity Tolerance: MacAdam 3 Beam Angle: 17° LOR: 68% Average Service Life: 50000h LED reliability: >53000h L80B50 UGR: <19 under the below indicated parameters Room dimensions X=4H/8H Reflectance 20% | 50% | 70% Luminaire spacing = 0.5m Photobiological safety group: 1



This product contains a light source of energy efficiency class E

Electronic Equipment S: On/Off

Luminaire efficiency: 86 lm/W

*Add the suffix -S after the reference to indicate your electronic equipment choice.

Finishes .50 Golden:

Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 26.04.2024]

5 years guarantee

BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L.

Pol. Ind. La Gavarra

Spain

08540 Centelles | Barcelona

Ronda de la Font Grossa, 15

Contact

T. +34 93 881 35 12 T. +34 93 881 37 13 info@rovasi.com www.rovasi.com