
# STYLE Small recessed downlights







## 151STY.50-R1081



Recessed ceiling-mounted downlights with symmetrical light distribution to achieve an effective task or ambient lighting.

Round design in diameter 55mm.


Die-cast aluminium trim liquid-painted in appealing textured finishes.

Accessory available to increase the protection rating to IP44 from underneath [reference M2.A0035]. Honeycomb anti-dazzle screen accessory to increase visual comfort [reference M6.A0035]. Remote driver included.

The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM  $\leq$  1 and SVM  $\leq$  0.4.

Passive temperature management: heat dissipation via aluminium heat sink. Ceiling-mounted using galvanised steel support with spring clamps.

Luminaire luminous flux: 760lm Luminaire connected power: 9.41 W Luminaire efficiency: 81 lm/W Light source luminous flux: 1085lm Light source power: 8.5 W Constant Current: 250 mA **CRI:** >90 Colour Temperature: 2700K Chromaticity Tolerance: MacAdam 3 Beam Angle: 28° LOR: 70% LED reliability at nominal Ta = 25°C: >53000h L80B50 UGR: <19 under the below indicated parameters Room dimensions X=4H/8H Reflectance 20% | 50% | 70% Luminaire spacing = 0.7m



Photobiological safety group: 1 This product contains a light source of energy efficiency class E

**Electronic Equipment** S: On/Off

\*Add the suffix -S after the reference to indicate your electronic equipment choice.

Finishes .50 Golden:

Upgradeable, Replaceable, Repairable



#### Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 03.07.2025]

## 5 years guarantee

BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

### **ROVASI S.L.**

Pol. Ind. La Gavarra

Spain

08540 Centelles | Barcelona

Contact Ronda de la Font Grossa, 15

T. +34 93 881 35 12 T. +34 93 881 37 13 info@rovasi.com www.rovasi.com